

SOLAR LIGHTING AND SECURITY TOWER













1x 4MP 25x PTZ * 1x 4.8 to 120mm Adjustable Focal * 4 weeks continuous recording on 4TB Hard Drive Phone App or PC/Cloud Scheduled recordings, Email/ App alerts, Movement/Smart event detection, false alarm reduction/vehicle-person recognition.

ECO CCTV GP28 K GENERAL

- Model Lumen Output Mast Height Mast Type Lights Trailer Type Tyre and Rim Size Stabilizer Supports Mudguard / Wheel Chock Features
- ECO CCTV GP28k 28,000 25 Feet Hydraulic/Cable 1x 150w LED Modules Single Axle 215/70R15 4 x Manual Included Folding Draw bar, 7 day Timer/ Day Night modes, Fire Extinguisher, Emergency Stop, Battery Isolator, Adjustable Solar Tilt, Security wheel nuts, AC Charger.

CAMERA

LENS

Camera Quality

Recording Time

Monitoring

Features

OPERATIONAL DATA

Wind Rating Working Temperature 60mph 32°F to 122°F

BATTERY

Battery Runtime Solar Solar Tilt Efficiency (solar)

UNIT

Dimensions (Towing) Dimensions (Deployed) Dimensions (Stowed) Weight 10.8kWh Deep Cycle Gell
30 Hours
1.23kWp
30° to 45°
1 hour of sun/3 hours of operation

123.6" x 59.0" x 114.2" (LxWxH) 86.6" x 136.0" x 301.2" (LxWxH) 86.6" x 59.0" x 114.2" (LxWxH) 2866 lbs



WWW.COREPROJECTSENERGY.COM

*Multiple camera types available. NDAA compliant available upon customer request.

+1 (210) 290-9624